



NOTE: 1) HYDRO @ 390 PSIG. MIN.

|  |                    |
|--|--------------------|
| SHELL / HEADS                            |                    |
| .166" SA-414-G                           | 2.1: S.E.          |
| JOGGLE                                   |                    |
| .200" SA-455                             |                    |
| M.A.W.P.                                 | 300 PSIG. @ 400 °F |
| M.D.M.T.                                 | -20 °F @ 300 PSIG. |
| ASME: SECTION VIII DIV. 1, 2001 ADD 2002 |                    |
| X-RAY:                                   | RT-NO              |
| GALLONS:                                 | 80                 |
| WT.                                      | 263 LBS.           |
| SERIAL NO.                               |                    |
| N.B.                                     |                    |

|                               |                 |                |
|-------------------------------|-----------------|----------------|
| 20-VD-80-F                    |                 | REV. 9-2-03    |
| FOR: HANSON STANDARD          |                 | DATE: 11-28-89 |
| VERT. AIR TANK                |                 |                |
| INSIDE: UNPAINTED             |                 |                |
| OUTSIDE: PRIME                |                 |                |
| BY: J.G.                      | SCALE: 3/4"=12" |                |
| <b>ROY F. HANSON JR. MFG.</b> |                 |                |
| 1924 COMPTON AVE.             |                 |                |
| LOS ANGELES, CA 90011         |                 |                |