



SHELL / HEADS	
M.A.W.P.	550 PSIG. @ 400 °F
M.D.M.T.	-20 °F @ 550 PSIG.
ASME SECTION VIII	DIV. 1, 2001 ADD 2002
X-RAY:	RT-4 SPOT L.S. & HDS. G.S.
GALLONS:	240
SERIAL NO.	WT. 1244 LBS.
N.B.	

  

NOTE: 1) HYDRO @ 715 PSIG. MIN.	
2) PRE HEAT BEFORE WELDING TO 150°F	
.401" SA-455 2:1 S.E.	
(.390" MIN.) TRIM	
.500" SA-516-70	
M.A.W.P. 550 PSIG. @ 400 °F	
M.D.M.T. -20 °F @ 550 PSIG.	
ASME SECTION VIII DIV. 1, 2001 ADD 2002	
X-RAY: RT-4 SPOT L.S. & HDS. G.S.	
GALLONS: 240	
SERIAL NO. WT. 1244 LBS.	
N.B.	

  

30-VK-240-F	REV. 12-24-02
FOR: HANSON STANDARD	DATE: 7-8-85
VERT. AIR TANK	
INSIDE: UNPAINTED	
OUTSIDE: PRIME	
CAD-"B" SIZE UNDER "STD"-SERIES	
BY: J.G.	SCALE: 1"=12"
<b>ROY E. HANSON JR. MFG.</b>	
1924 COMPTON AVE.	
LOS ANGELES, CA 90011	

NOTE: 1) HYDRO @ 715 PSIG. MIN.  
2) PRE HEAT BEFORE WELDING TO 150°F

