



VIEW W/OUT SUPPORTS

NOTE: 1) HYDRO @ 260 PSIG. MIN.
 2) FOR CANADIAN SHIPMENT ADD C.R.N. D-7289.213.

HEADS		.140" SA-414-G 2:1 S.E.	
JOGGLE			
SHELL		.165" SA-414-G	
M.A.W.P.	200 PSIG. @ 400 °F		
M.D.M.T.	-20 °F @ 200 PSIG.		
ASME. SECTION VIII DIV. 1, 2001 ADD. 2002			
X-RAY:	RT-NO		
GALLONS:	60	WT.	231 LBS.
SERIAL NO.			
N.B.			
H-60-FP		REV.	2-6-03
FOR: HANSON STANDARD		DATE:	3-9-62
HORIZ. AIR TANK			
U.S.C.G. APPROVED			
INSIDE: UNPAINTED			
OUTSIDE: PRIME			
BY: E.S.	SCALE: 1"=12"		
ROY E. HANSON JR. MFG.			
1924 COMPTON AVE.			
LOS ANGELES, CA 90011			

PLATFORM PER:
 SK-640 REV.-2

2"R W/ C.I. PLUG
 INSP. OPENING
 (2) PLC'S.

(4) 3"LG. WELDS
 EA. SIDE
 TYP.

(3) SIDES EA.
 WELD
 TYP.