



1/4" THK. CLIPS PER  
 MA-395-B (4) PLC'S  
 W 9/16" Ø HOLE ON  
 32 1/2" B.C.; WELD OUTSIDE  
 VERT. EDGE OF CLIP ONLY

NOTE: 1) HYDRO @ 390 PSIG. MIN.

HEADS	.337" SA-455 2:1 S.E.	0-36-VD-400-R	REV.
	(.293" MIN.) TRIM		DATE: 7-19-04
SHELL	.3125" SA-455	FOR: HANSON STANDARD	
	(.296" MIN.)	VERT. AIR TANK	
M.A.W.P.	300 PSIG. @ 200 °F	SURFACE AREA = 81.3 SQ. FT.	
M.D.M.T.	-20 °F @ 300 PSIG.	INSIDE: EPOXY LINED	
ASME. SECTION	VIII DIV. 1, 2001 ADD 2003	OUTSIDE: PRIME	
X-RAY:	RT-4 SPOT L.S.	CAD-"B" SIZE UNDER "O"-SERIES	
GALLONS:	400	WT. 1211 LBS.	BY: J.G. SCALE: 3/4" = 12"
SERIAL NO.		<b>ROY E. HANSON JR. MFG.</b> 1924 COMPTON AVE. LOS ANGELES, CA 90011	
N.B.			