



NOTE: 1) HYDRO @ 520 PSIG. MIN.

|                                  |               |                       |          |
|----------------------------------|---------------|-----------------------|----------|
| SHELL / HEADS                    |               | .200" SA-455 2:1 S.E. |          |
| TRIM                             |               |                       |          |
| .240" SA-455                     |               |                       |          |
| M.A.W.P.                         | 400 PSIG. @   | 400 °F                |          |
| M.D.M.T.                         | -20 °F @      | 400 PSIG.             |          |
| ASME SECTION VIII DIV. 1, 2001   |               |                       |          |
| X-RAY:                           | RT-NO         | WT.                   | 313 LBS. |
| SERIAL NO.                       |               |                       |          |
| N.B.                             |               |                       |          |
| 18-HJ-73-W                       |               | REV.                  | 10-2-02  |
| FOR: HANSON STANDARD             |               | DATE:                 | 4-27-81  |
| HORIZ. AIR TANK                  |               |                       |          |
| INSIDE: UNPAINTED                |               |                       |          |
| OUTSIDE: PRIME                   |               |                       |          |
| CAD-"B" SIZED UNDER "STD"-SERIES |               |                       |          |
| BY: J.G.                         | SCALE: 1"=12" |                       |          |
| <b>ROY E. HANSON JR. MFG.</b>    |               |                       |          |
| 1924 COMPTON AVE.                |               |                       |          |
| LOS ANGELES, CA 90011            |               |                       |          |